

SAFETY DATA SHEET (SDS) RUST PROTECTION BLACK

SECTION 1: IDENTIFICATION

Product Name: Product Use: Product Code(s): Rust Protection Black Black Petroleum Rust Inhibitor S-100B, S-160B, S120B, S-101B

Supplier:

Sym-Tech Inc. P.O. Box 430, Stn A Scarborough ON M1K 5C3 1-800-363-5796 **Emergency Tel.**

1-613-996-6666 CANUTEC for 24HR emergency information

SECTION 2: HAZARD(s) IDENTIFICATION

GHS HAZARD CLASSIFICATION: Classification of Substance of mixture: Flam. Liq 3;H226 Aspiration Hazard 1; H304 Skin Irritant 2; H315 Eye Irritant 2B; H320 STOT, SE. 3; H336	Flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes eye irritation May cause drowsiness or dizziness
LABEL ELEMENTS: Signal Word: H226	Danger Flammable Liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H320	Causes eye irritation
H336	May cause drowsiness and dizziness
Symbol	

Prevention:	
P210+P260	Keep away from heat/sparks/open flames/hot surfaces - do not smoke during use of product. Do not breathe dust/fume/gas/mist/vapours/spray.
P240	Ground/bond container and receiving equipment
P241 P242	Use explosion –proof electrical/ventilating/light equipment Use only non-sparking tools
P243	Take precautionary measure against static discharge
P264	Wash thoroughly after handling
P270	Do not eat, drink, or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/eye protection/face protection. Use only outdoors or in a well ventilated area.
Response:	
P302+352 – If on Skin:	Wash with plenty of soap and water
P304+361+338 – If on Skin or hair:	Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
P340+P304+P312– If Inhaled:	Remove victim to fresh air and keep at rest in a position comfortable to breathe. Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338 – If in Eyes:	Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P370 + 378 If Swallowed:	Immediately call a poison center or a doctor. DO NOT INDUCE VOMITING.
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P13	If eye irritation occurs: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P370+P378	In case of fire: Use extinguishing media listed in Section 5 of SDS for Extinction.
P391	Collect spillage
Storage:	
P403+P233	Store in a well ventilated place. Keep container tightly closed
P40	Store locked
Disposal:	
P501	Dispose contents/container in accordance with local/national regulations

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredients / Chemical Designations	Weight %	GHS Classification	Notes
Stoddard solvent	15 - 40	STOT RE 1;H372	(1) (2)
CAS Number (0008052-41-3		Asp. Tox 1;H304	

In accordance with paragraph (1) of 1910.1200, the specific chemical identity and / or exact percentage (concentration) of composition has been withheld as a trade secret

- 1) Substance classified with a health or environmental hazard
- 2) Substance with a workplace exposure limit
- 3) PBT-substance or vPvB-substance

* The full texts of the phases as shown on Section 16

SECTION 4: FIRST-AID MEASURES

General:	In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Skin: Moderately irritating. Ingestion: Abdominal irritation Inhalation: If enlivened by primer or heat, over exposure to fume could cause irritation, dizziness.
Inhalation:	Move the victim to fresh air. If breathing is difficult give oxygen. If breathing has stopped give artificial respiration. Seek immediate medical attention.
Skin:	Remove the paint residue using industrial hand cleaner. Wash the skin with plenty of warm water and mild nonabrasive soap for at least 15 minutes. Do not use cold water. Remove contaminated clothes, wash clothing before reuse. If the irritation persists repeat the washing procedure. Seek medical attention.
Eyes:	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Ingestion:	DO NOT induce vomiting. Keep the victim warm and quiet. Seek immediate medical attention. Should vomiting occur, lean the victim over to reduce the risk of aspiration.

Most important symptoms and effects, both acute and delayed Overview:	
Effects of Over exposure:	
Inhalation:	Excessive exposure to vapors may be irritating to the nose, throat, upper respiratory tract and lungs. Excessive exposure can result in headaches, dizziness, nausea, and narcotic effects; it can be defined as inadequate ventilation for extended periods of time.
Eye Contact:	Splash of the liquid or concentrated vapours may cause severe eye irritation. Severe injuries may result of repeated or prolonged contact. Injuries to the eye may be permanent if not treated.
Skin Contact:	May be irritating to the skin, causing defatting, redness, cracking and dryness. Toxic amounts of product may be absorbed through the skin.
Ingestion:	If swallowed, this product may cause vomiting, nausea and diarrhea and may be harmful if swallowed in very large amounts.
Chronic Exposure:	Prolonged skin contact may cause dermatitis

Exposure to solvent vapor concentrations from the components solvents in excess of the stated occupational exposure limits may result in adverse effects on the kidneys, liver, and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

SECTION 5: FIRE-FIGHTING MEASURES

Explosion Data:	Sensitivity to mechanical impact: Not Sensitive Sensitivity to static charge: Sensitive
Extinguishing Media:	Class B dry chemical carbon, carbon dioxide or other suitable extinguishing material such as dry sand. Do not use halogenated agents. When flames have been eliminated, cover residue with dry extinguishing agent or dry sand and allow it to remain undisturbed until it has cooled. If fire appears to increase in intensity stop using these agents. Apply Class D extinguishing agent or more dry inert, granular material. Ring fire with extinguishing material and allow the fire to burn out.
Special hazards arising from the substance or mixture:	Hazardous decomposition: Oxides of carbon Keep away from heat/sparks/open flames/hot surfaces – do not smoke Keep cool Ground/bond container and receiving equipment Use explosive-proof electrical/ventilating/light/ equipment. Use only non-sparking tools Take precautionary measures against static discharge Do not breathe mist / vapors / spray Do not get in eyes, on skin, or on clothing
Advice for Fire Fighters:	Treat as a highly flammable liquid. Wear self-contained breathing apparatus. Wear complete protective clothing (overalls, boots, goggles, etc.) and safety equipment. Evacuate area and fight fire from a safe distance. Vapours from an explosive mixture between upper and lower explosion limits in air (percent volatiles in air). If the fire does not respond to the above agents or they are not available, use foam or water FOG as a last result. Water may also be used to cool exposed, but not burning, containers. These products may float and be re- ignited on top of water. Closed containers may explode in a fire. Keep containers cool and remove to a safe location. In a confined space, wear positive pressure, self- contained breathing apparatus (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Put on appropriate personal protective equipment (see section 8)
Environmental Precautions:	Do not allow spills to enter drains or waterways Use good personal hygiene practices. Wash hands before eating, drinking smoking or using a toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
Methods and material for containment and clean up:	Remove any sources of ignition and avoid prolonged breathing of vapour when preforming and cleaning up spills. Ventilate the area. Absorb the spill by using an inert material (sand, earth, vermiculate etc.) Transfer the absorbed material in a waste container. Handle as a highly flammable liquid. Prevent the product or any wash waters from entering the water system or sewers. Wear a NIOSH/OSHA approved organic vapour canister respirator. Wear protective clothing such as safety eyewear, overalls, impervious boots and chemical resistant gloves.

SECTION 7: HANDLING AND STORAGE

Storage:	Store in cool, dry area, away from heat, sparks and naked flames.
	Keep container sealed when not in use. Keep container
	closed when not in use. Store in a dry ventilated area. Maintain package labeling during storage.
	Incompatible materials: Can react violently with strong oxidizing agents, alkalis, and acids. Store in a cool, dry, well-ventilated area. Keep away from direct sunlight, high heat, incompatible material and any sources if ignition.
Handling:	Always ground the containers when transferring or mixing. See section 2 for further details (Prevention)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure:

CAS No.	Ingredient	Source	Value
0008052-41-3	Stoddard Solvent	OSHA	TWA 500 ppm (2900 mg/m3)
		ACGIH	TWA: 290 mg/m3 STEL: 580 mg/m3
		NIOSH	TWA 350 mg/m3 C 1800 mg/m3 (15 minutes)

Carcinogen Data:

CAS No.	Ingredient	Source	Value
0008052-41-3	Stoddard Solvent	OSHA	Select Carcinogen: No
		ACGIH	Known: No; Suspected: No
		NIOSH	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No

Respiratory Protection:	Avoid breathing the vapour. Use an organic vapour mask under normal conditions and use a NIOSH/OSHA approved organic vapour canister respirator when exposure levels are exceeded. Use adequate ventilation. Engineering: provide sufficient ventilation to control the exposure levels below limits.
Skin Protection:	Protective clothing as necessary to prevent wetting of the skin
Eye Protection:	Wear anti-splash chemical goggles with side shields or wear a full face shield. Contact lenses should not be worn when working around organic solvents.
Engineering Controls:	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices:	Avoid repeated or prolonged contact with skin. If rags are used with this product as a cleaning purpose, discard them into a water-filled container after use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. See section 2 for further details (Prevention)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear Liquid
Odour:	Petroleum Odour
Odour Threshold:	Not determined
pH:	Not Measured
Melting Point / Freezing Point:	Not Measured
Initial Boiling point and boiling range:	>154°C >310°F
Flash Point:	>41°C >°106°F (TCC)
Evaporation rate (Ether = 1):	Slower then N-Butyl Alcohol
Flammability (solid, gas):	Not applicable
Upper / Lower flammability or explosive limits:	Not available
Vapour Pressure (Pa):	Not available
Vapour Density:	Not available
Specific Gravity:	0.887 @ 77°F
Solubility in Water:	Insoluble
Partition Coefficient n-octanol/water (Log kow):	Not measured
Auto-ignition Temperature:	Not available
Decomposition Temperature:	Not measured
Viscosity (cSt):	Not available
VOC Content:	386g/L (typical)
Percent Solids (by weight):	56% (typical)
Percent Volatile (by weight):	44% (typical)
Percent Solids (by volume):	54% (typical)
Density (lbs/US gal):	7.389 (typical) @ 77°F

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Reactivity: Possibility of Hazardous Reactions: Materials to Avoid: Conditions to Avoid: Hazardous Decomposition Products: Stable under normal circumstances Hazardous Polymerization will not occur No data available Strong oxidizing agents, alkalis and acids Sparks and open flames, high heat, direct sunlight Oxides of carbon

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity:

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupation exposure limits may result in adverse health effects as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50 mg/kg	Skin LD50 mg/kg	Inhalation Vapour LC50, mgL/4hr	Inhalation Dust/ Mist LC50 mg/L/4hr	Inhalation Gas LC50 ppm
Stoddard Solvent	>5,000.00, Rat -	No data	No data	>5.50 Rat - Category	No Data
(8052-41-3	Category: NA	available	available	NA	available

Note: When no route specific LD50 data is available for an acute toxic, the converted acute toxicity point estimate was used in the calculation of the products ATE (Acute Toxicity Estimate)

Classification	Category	Hazard Description
Acute Toxicity (oral)		Not Applicable
Acute Toxicity (dermal)		Not Applicable
Acute Toxicity (inhalation)		Not Applicable
Skin corrosion / irritation	2	Causes skin irritation
Serious eye damage / irritation	2B	Causes eye irritation
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT – single exposure	3	May cause drowsiness or dizziness
STOT – repeated exposure		Not applicable
Aspiration Hazard	1	Mat be fatal if swallowed and enters airways

Page 10 of 12

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: No additional information is provided for this product. See section 3 for chemical specific data

Aquatic Ecotoxicity:

Ingredient	96 hr LC 50 fish, mg/l	48 hr EC50 crustacea mg/l	Inhalation Vapour LC50, mgL/4hr
Stoddard Solvent - (8052-41-3)	Not available	Not available	No available

Persistence and degradability: There is no data available on the preparation itself

Bioaccumulative Potential: Not Measured

Mobility in Soil: No data available

Results of PBT and vPvB assessment: This product contains no PBT/vPvB chemicals

Other adverse effects: No data

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods:

Observe all federal, state, provincial and local regulations when disposing of this substance.

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO / IATA
UN Number	Not Applicable	Not Regulated	Not Regulated
UN Proper Shipping Name	Not Regulated	Not Regulated	Not Regulated
Transport Hazard Class	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
Packing Group	Not Applicable	Not Applicable	Not Applicable
Environmental Hazards IMDG	Marine pollutant: No further information		
Special Precautions for User	No further information		

SECTION 14: TRANSPORT INFORMATION

SECTION 15: REGULATORY INFORMATION

Regulatory Overview:	The regulatory data in Section 15 is not intended to be all inclusive, only selected regulations are represented
Toxic Substance Control Act (TSCA):	All components of this material are either listed or exempt from listing on the TSCA inventory
WHIMIS Classification: US EPA Tier II Hazards	B3 D2A
Fire: Sudden Release of Pressure: Reactive: Immediate (acute): Delayed (chronic)	Yes No No No
EPCRA 311/312 Chemicals and RQ's (lbs):	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
EPCRA 302 Extremely Hazardous	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
EPCRA 313 Toxic Chemicals:	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
Proposition 65 – Carcinogens (> 0.0%):	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
Proposition 65 – Developmental Toxins (> 0.0%):	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
Proposition 65 – Female Repro Toxins (> 0.0%):	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
Proposition 65 – Male Repro Toxins (> 0.0%):	To the best of our knowledge, there are no chemicals at levels which require reporting under this statue
New Jersey RTK Substances (> 1%):	Stoddard solvent
Pennsylvania RTK Substances (> 1%):	Stoddard solvent

SECTION 16: PREPARATION AND OTHER INFORMATION

The full text of the phrases appearing in section 3 is:

H226 H304	Highly flammable liquid and vapor May be fatal is swallowed and enters airways
H315	Causes skin irritation
H320	Causes eye irritation
H336	May causes drowsiness and dizziness
PREPARED BY:	WHMIS Committee
PHONE NUMBER:	1-800-363-5796
EMERGENCY:	This SDS is Registered with CANUTEC
EMERGENCY NUMBER:	For 24hr Information call 613-996-6666
PREPARATION DATE:	January 2018
EXPIRES:	January 2021

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Customers / users of this product must comply with all health and safety laws, regulations.