

SAFETY DATA SHEET (SDS) RUST PROTECTION WATERBASED - BLACK

SECTION 1: IDENTIFICATION

Product Name: Rust Protection – Waterbased Black

Product Use: Automotive Coatings

Product Code(s): S-600WBB, S-660WBB, S-620WBB, S-601WBB

Supplier:

Sym-Tech Inc. P.O. Box 430, Stn A Scarborough ON M1K 5C3

1-800-363-5796

Emergency Tel. 1-613-996-6666 CANUTEC for 24HR emergency

information

SECTION 2: HAZARD(s) IDENTIFICATION

Classification of Substance of mixture:

Regulated in bulk only - UN1268 Petroleum Distillates, n.o.s (Naphtha (petroleum, hydrated heavy) Class 3 PG III - With an inner packaging < 450L, may be renamed "Non-Regulated" as per TDG 1.33.

LABEL ELEMENTS:

Signal Word: Danger

Symbol:



GHS Hazardous Statements:

H226: Flammable liquid and vapour

H302: Harmful if swallowed

H312: Harmful if contact with skin

H315: Causes skin irritationH320: Cause eye irritation

H332: Harmful if inhaled

H335: May cause respiatory irritation

H361: This product contains ingredients which are suspect to

damage fertility or unborn child

H373: May cause damage to the liver & kidneys through

prolonged or repeated contact

GHS Precautionary Statements:

P202: Do not handle this product until all safery instructions

have been read and understood

Section 2 Con'd Page 2 of 6

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233: Keep container tightly closed P235: Keep cool P240: Ground / bond container and receiving equipment P241: Use exposure –proof electrical / ventilating / light equipment P242: Use only non-sparking tools P243: Take precautionary measure against static discharge P261: Avoid breathing mists, vapours, and sprays P262: Do not get in eyes, on skin, or on clothing P264: Wash thoroughly after handling P270: Do not eat, drink, or smoke when using this product P271: Use only outdoors or in well ventilated areas P272: Contaminated work clothes should not be allowed out of the workplace

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

protection

Wear protective gloves / eye protection / face

This product contains the following substances:

P280:

Ingredients	Approximate Concentration	CAS#	LD50	LC50
Stoddard Solvent CAS Number: 0008052-42-4	> 10 %	8052-41-3	Oral LD50 Rat > 5000 mg/kg Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 Rat >5mg/L (4Hr Mist)
Waterbased Emulsion	> 20 %	8052-42-4	N/A	N/A

SECTION 4: FIRST-AID MEASURES

General:	In all cases of doubt or when symptoms persist, seek		
	medical attention.	Never give anything by mouth to an	

unconscious person. Use good hygiene habits.

Inhalation: Move the victim away from affected area to fresh air, if

needed give artificial respiration, seek medical attention. Immediately remove all contaminated clothing. Wash using plenty of water. If irritation persists seek medical

attention.

Eyes: Immediately flush for 15 minutes using plenty of water

and seek medical attention.

Ingestion: Do not induce vomiting. Contact physician or poison

control centre. For spontaneous vomiting have the victim lean forward with head down to reduce the risk of

aspiration. Seek Medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Flammable: Yes

Skin:

Conditions: Excessive heat, spark, open flame

Flash Point (TCC deg. F): 105 °F - 110 °F

Autoignition Temp (deg. F): 210 ° F
Upper Flammability Limits in the Air (% vol): 7.5
Lower Flammability Limits in the Air (% vol): 1.0
Rate of Burning: N/A

Hazardous Combustion Products: Oxides of Carbon (CO, CO2)

Explosive Power: N/A

Sensitivity to Mechanical Impact: N/A – Not Expected **Sensitivity to Static Discharge:** N/A – Not Expected

Means of Extinction: 'Alcohol" foam, CO2, dry chemical. In case of larger fires,

water spray should be used

SECTION 6: ACCIDENTAL RELEASE MEASURES

Evacuation Procedures & Safety: Wear appropriate protective gear for the situation. See

Personal Protection Information in Section 8

Containment of Spill: Retain diluted water for later disposal. Follow procedure

below under Cleanup and Disposal of spill.

Cleanup & Disposal of Spill: Always exercise caution & wear personal safety

protection when dealing with chemicals. Eliminate all sources of ignition. Prevent runoff into drains, sewers, and other waterways. Contain diluted material into empty drums & call in the appropriate Government

authorities for disposal.

Environmental & Regulatory Reporting:Large spills should be handled according to a

predetermined plan. No environmental effects reported.

SECTION 7: HANDLING AND STORAGE

Store and use in a cool dry environment. Keep away		
from heat, sparks, and open flames. Keep container		
closed when not in use. Store away from oxidizing and		

reducing materials. Store away from sunlight.

. .

Handling:Keep away from heat, spark and open flames. Containers must be grounded and bonded. Do not use near sources

of ignition. Do not cut, drill, weld, or grind near containers. Open containers slowly to allow for any

pressure build-up to escape.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Effects of Acute Exposure to Product: Vapours are irritating to eyes, nose, throat and

respiratory tract. Prolonged exposure to high vapour concentrations may cause headache. Prolonged and repeated contact may lead to dermatitis, may cause defatting, drying and cracking of the skin. Swallowing may cause burning sensation of the mouth and stomach.

Also may cause nausea and diarrhea.

Effects of Chronic Exposure to Product:Breathing high concentrations of vapour may cause

anesthetic and serious health effects. Intestinal misuse of this product may be harmful or fatal. Chronic

exposure to organic solvents may cause permanent brain

and nervous system damage.

Carcinogenicity: Asphalt may contain traces of Benzene, a chemical

known to cause cancer

Reproductive Effects of Material: Methanol is a teratogenic and embryotoxic in animals

Teratogenicity: Methanol is a teratogenic and embryotoxic in animals

Mutagenicity: N/A – No effects anticipated

Sensitization: N/A – No skin or respiratory sensitizer anticipated

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical State: Liquid - Clear / Black
Odor Threshold (ppm) Aromatic, 0.2 ppm

Vapour Density (Air = 1) 4.7
Vapour Pressure (mm Hg) NA

Boiling Point (Dec. C): 310 ° C - 393 ° C

Melting / Freezing Point (Deg. C):

NA
PH:

NA

Density: 0.90 lbs / gallon

% Volatile (G/L): 770.3

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal circumstances

Reactivity Conditions: Avoid heat, spark, and open flame. Explosive reactions can

occur in the presence of strong oxidizing agents.

Conditions to Avoid: Sparks and open flames, high heat. Direct sunlight

Hazardous Decomposition Products: Oxides of carbon

SECTION 11: TOXICOLOGICAL INFORMATION

Eye Contact:Can cause redness, irritation, tissue destruction **Effects of Chronic Exposure:**Prolonged or repeated contact may cause drying of

Prolonged or repeated contact may cause drying or cracking of the skin or eczema like rashes.

Ingestion Toxicity: Slightly toxic, can cause dizziness and headaches

Inhalation Toxicity: No test data found for product

Carcinogenicity of Material: This product does not contain any substances that are

considered by OSHA, NTP, IARC or ACGIH to be suspected human carcinogens. No additional data found for product.

SECTION 12: ECOLOGICAL INFORMATION

Environmental: Do not allow to enter waters, waste water or soil

Biodegradability: N/A

No other adverse effects found

SECTION 13: DISPOSAL INFORMATION

Keep spills / leaked product contained and call in appropriate government authorities for disposal.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name: Petroleum Distillates

UN Number: 1268
Class or Division: 3

Sub Risk: Not Applicable

Packing Group: III
Environmental Hazard: No

Note: With an inner packaging < 450L, may be renamed "Non-

Regulated"

Pennsylvania RTK Substances (> 1%): Asphalt (petroleum)

Methanol

Stoddard solvent

SECTION 15: REGULATORY INFORMATION

U.S Federal Regulations:

Occupational Safety & Health Administration (OSHA)

(29CFR 1910.1200 Hazard Category):

Irritant – Skin and eyes. Flammable

Toxic Substances Control Act (TSCA):All components are included on the TSCA inventory

Superfound Amendments and Rauthorization Act

None

(SARA) Title III Information:

SARA (EPCRA) Section 311/312 (40 CFR 370) Hazardous Categories:

Immediate Hazard:NoDelayed Hazard:NoFire Hazard:YesPressure Hazard:NoReactivity Hazard:No

State Regulations:

California: This product contains the following chemical(s) known to

cause cancer, birth defects or reproductive harm:

COMPONENT	CAS#	CONCENTRATION
Mineral Spirits	8052-41-3	0.1 – 1.0

International Regulations:

Canadian Workplace Hazardous Materials Information System: (WHIMIS): B3. D2A. D2B

This product contains the following toxic chemical(s) subject to reporting requirements of SARA (EPCRA) Section 313 (40 CFR 372)

This product contains the following components in concentrations greater the 0.0% for carcinogenic substances and / or 1.0% of the substances subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and reauthorization Act of 1986 and 40 CFR Part 372.

1,2,4 Trim ethylbenzene (CASRN 95-63-6): 2.7 %

SECTION 16: PREPARATION AND OTHER INFORMATION

PREPARED BY: WHMIS Committee PHONE NUMBER: 1-800-363-5796

EMERGENCY: This SDS is Registered with CANUTEC **EMERGENCY NUMBER:** For 24hr Information call 613-996-6666

PREPARATION DATE:January 2021EXPIRES:January 2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Customers / users of this product must comply with all health and safety laws, regulations.